

Beam Power Tube

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts.	1.2	amp

Direct Interelectrode Capacitances


(Approx.):^a

Grid No.1 to plate.	0.6	μf
Grid No.1 to cathode & grid No.3, grid No.2, and heater	13	μf
Plate to cathode & grid No.3, grid No.2, and heater	8.5	μf

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-5/8"
Maximum Seated Length.	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" ± 3/32"
Diameter.	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW.	7CV

Pin 1 - Cathode,
Grid No.3
Pin 2 - Grid No.1
Pin 3 - Heater



Pin 4 - Heater
Pin 5 - Grid No.1
Pin 6 - Grid No.2
Pin 7 - Plate

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	150	max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	130	max.	volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:			
Positive-bias value	0	max.	volts
PLATE DISSIPATION	7	max.	watts
GRID-No.2 INPUT	1.4	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 ^b	max.	volts
BULB TEMPERATURE (At hottest point on bulb surface).	220	max.	°C

← Indicates a change.



6CU5

Typical Operation and Characteristics:

Plate Voltage	120	volts
Grid-No.2 Voltage	110	volts
Grid-No.1 Voltage	-8	volts
Peak AF Grid-No.1 Voltage	8	volts
Zero-Signal Plate Current	49	ma
Max.-Signal Plate Current	50	ma
Zero-Signal Grid-No.2 Current	4	ma
Max.-Signal Grid-No.2 Current	8.5	ma
Plate Resistance (Approx.)	10000	ohms
Transconductance	7500	μ hos
Load Resistance	2500	ohms
Total Harmonic Distortion	10	%
Max.-Signal Power Output	2.3	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max.	megohm
For cathode-bias operation	0.5 max.	megohm

^a without external shield.

^b The dc component must not exceed 100 volts.






6CU5

6CU5

AVERAGE CHARACTERISTICS



TUBE DIVISION

92CM-8908RI

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

6CU5



6CU5

OPERATION CHARACTERISTICS

